

XBD

Long Shaft Vertical Turbine Fire Pump



MODEL	Power		Flow		Head		Port
	z		L/s	m3/h	Mpa	m	mm
XBD 3.2/ 1WJ	1.5	2	1	3.6	0.32	32	50
XBD 4.0/ 1WJ	1.5	2	1	3.6	0.40	40	50
XBD 5.0/ 1WJ	2.2	3	1	3.6	0.50	50	50
XBD 6.0/ 1WJ	2.2	3	1	3.6	0.60	60	50
XBD 7.0/ 1WJ	3	4	1	3.6	0.70	70	50
XBD 8.0/ 1WJ	3	4	1	3.6	0.80	80	50
XBD 9.0/ 1WJ	3	4	1	3.6	0.90	90	50
XBD 10.0/ 1WJ	3	4	1	3.6	1.00	100	50
XBD 11.0/ 1WJ	4	5.5	1	3.6	1.10	110	50
XBD 12.0/ 1WJ	4	5.5	1	3.6	1.20	120	50
XBD 13.0/ 1WJ	4	5.5	1	3.6	1.30	130	50
XBD 14.0/ 1WJ	4	5.5	1	3.6	1.40	140	50
XBD 15.0/ 1WJ	5.5	7.5	1	3.6	1.50	150	50
XBD 16.0/ 1WJ	5.5	7.5	1	3.6	1.60	160	50
XBD 17.0/ 1WJ	5.5	7.5	1	3.6	1.70	170	50
XBD 3.2/ 3WJ	2.2	3	3	10.8	0.32	32	50
XBD 4.0/ 3WJ	3	4	3	10.8	0.40	40	50
XBD 5.0/ 3WJ	4	5.5	3	10.8	0.50	50	50
XBD 6.0/ 3WJ	4	5.5	3	10.8	0.60	60	50
XBD 7.0/ 3WJ	5.5	7.5	3	10.8	0.70	70	50
XBD 8.0/ 3WJ	5.5	7.5	3	10.8	0.80	80	50
XBD 9.0/ 3WJ	5.5	7.5	3	10.8	0.90	90	50
XBD 10.0/ 3WJ	7.5	10	3	10.8	1.00	100	50
XBD 12.0/ 3WJ	7.5	10	3	10.8	1.20	120	50
XBD 13.0/ 3WJ	11	15	3	10.8	1.30	130	50
XBD 15.0/ 3WJ	11	15	3	10.8	1.50	150	50
XBD 16.0/ 3WJ	15	20	3	10.8	1.60	160	50
XBD 17.0/ 3WJ	15	20	3	10.8	1.70	170	50
XBD 20.3/ 3WJ	15	20	3	10.8	2.03	203	50
XBD 3.2/ 5WJ	4	5.5	5	18.0	0.32	32	50
XBD 4.0/ 5WJ	4	5.5	5	18.0	0.40	40	50
XBD 4.5/ 5WJ	5.5	7.5	5	18.0	0.45	45	50
XBD 5.0/ 5WJ	5.5	7.5	5	18.0	0.50	50	50
XBD 5.5/ 5WJ	5.5	7.5	5	18.0	0.55	55	50
XBD 6.0/ 5WJ	5.5	7.5	5	18.0	0.60	60	50
XBD 6.5/ 5WJ	7.5	10	5	18.0	0.65	65	50
XBD 7.0/ 5WJ	7.5	10	5	18.0	0.70	70	50
XBD 7.5/ 5WJ	7.5	10	5	18.0	0.75	75	50
XBD 8.0/ 5WJ	7.5	10	5	18.0	0.80	80	50
XBD 8.5/ 5WJ	7.5	10	5	18.0	0.85	85	50
XBD 9.0/ 5WJ	11	15	5	18.0	0.90	90	50
XBD 9.5/ 5WJ	11	15	5	18.0	0.95	95	50
XBD 10.0/ 5WJ	11	15	5	18.0	1.00	100	50
XBD 11.0/ 5WJ	11	15	5	18.0	1.10	110	50
XBD 12.0/ 5WJ	15	20	5	18.0	1.20	120	50
XBD 13.0/ 5WJ	15	20	5	18.0	1.30	130	50
XBD 14.0/ 5WJ	15	20	5	18.0	1.40	140	50
XBD 15.0/ 5WJ	15	20	5	18.0	1.50	150	50
XBD 16.0/ 5WJ	18.5	25	5	18.0	1.60	160	50
XBD 17.0/ 5WJ	18.5	25	5	18.0	1.82	182	50
XBD 3.2/ 5GJ	4	5.5	5	18.0	0.32	32	50
XBD 4.0/ 5GJ	5.5	7.5	5	18.0	0.40	40	50
XBD 5.1/ 5GJ	5.5	7.5	5	18.0	0.51	51	50
XBD 5.6/ 5GJ	7.5	10	5	18.0	0.56	56	50
XBD 6.0/ 5GJ	7.5	10	5	18.0	0.60	60	50
XBD 7.0/ 5GJ	7.5	10	5	18.0	0.70	70	50
XBD 8.0/ 5GJ	11	15	5	18.0	0.80	80	50
XBD 9.8/ 5GJ	11	15	5	18.0	0.98	98	50
XBD 10.4/ 5GJ	11	15	5	18.0	1.04	104	50
XBD 11.0/ 5GJ	15	20	5	18.0	1.10	110	50
XBD 12.6/ 5GJ	15	20	5	18.0	1.26	126	50
XBD 13.0/ 5GJ	15	20	5	18.0	1.30	130	50
XBD 14.5/ 5GJ	15	20	5	18.0	1.45	145	50
XBD 16.5/ 5GJ	18.5	25	5	18.0	1.65	165	50
XBD 3.0/ 10GJ	7.5	10	10	36.0	0.30	30	100
XBD 3.9/ 10GJ	7.5	10	10	36.0	0.39	39	100

Applications:

Vertical Turbine Pumps are commonly used in various types of applications, from fire fighting use to moving process water in industrial plants to providing flow for cooling towers at power plants, from pumping raw water for irrigation, to boosting water pressure in municipal pumping systems, and for virtually every other imaginable pumping application. This pump is one of the most popular types of pumps for designers, end-users, installing Contractors, and distributors.

Features:

- Max Flow Capacity: 70 l/s (1000GPM)
- Max Head/Pressure: 1.85 Mpa (185m)
- Port DN: 50, 100, 150
- Max Power: 132KW
- Motor: Pure Copper Wire, with overheating protection
- Pump Case: Anti-corrosive coating Cast Iron
- Shaft: Stainless Steel. The radial runout of the shaft is controlled within 0.13mm of the US standard.
- Impeller: Stainless Steel

XBD

Long Shaft Vertical Turbine Fire Pump

MODEL	Power		Flow		Head		Port
	z		L/s	m3/h	Mpa	m	mm
XBD 4.2/ 10GJ	11	15	10	36.0	0.42	42	100
XBD 5.3/ 10GJ	11	15	10	36.0	0.53	53	100
XBD 6.0/ 10GJ	11	15	10	36.0	0.60	60	100
XBD 6.7/ 10GJ	15	20	10	36.0	0.67	67	100
XBD 7.0/ 10GJ	15	20	10	36.0	0.70	70	100
XBD 8.1/ 10GJ	15	20	10	36.0	0.81	81	100
XBD 8.5/ 10GJ	15	20	10	36.0	0.85	85	100
XBD 9.1/ 10GJ	18.5	25	10	36.0	0.91	91	100
XBD 10.9/ 10GJ	18.5	25	10	36.0	1.09	109	100
XBD 11.2/ 10GJ	22	30	10	36.0	1.12	112	100
XBD 13.0/ 10GJ	22	30	10	36.0	1.30	130	100
XBD 13.7/ 10GJ	22	30	10	36.0	1.37	137	100
XBD 14.3/ 10GJ	30	40	10	36.0	1.43	143	100
XBD 16.5/ 10GJ	30	40	10	36.0	1.65	165	100
XBD 18.5/ 10GJ	37	50	10	36.0	1.85	185	100
XBD 4.0/ 15GJ	11	15	15	54.0	0.40	40	100
XBD 5.0/ 15GJ	15	20	15	54.0	0.50	50	100
XBD 6.0/ 15GJ	15	20	15	54.0	0.60	60	100
XBD 6.4/ 15GJ	18.5	25	15	54.0	0.64	64	100
XBD 7.0/ 15GJ	18.5	25	15	54.0	0.70	70	100
XBD 7.8/ 15GJ	18.5	25	15	54.0	0.78	78	100
XBD 8.0/ 15GJ	22	30	15	54.0	0.80	80	100
XBD 9.2/ 15GJ	22	30	15	54.0	0.92	92	100
XBD 10.0/ 15GJ	22	30	15	54.0	1.00	100	100
XBD 10.6/ 15GJ	22	30	15	54.0	1.06	106	100
XBD 11.0/ 15GJ	30	40	15	54.0	1.10	110	100
XBD 12.0/ 15GJ	37	50	15	54.0	1.20	120	100
XBD 13.4/ 15GJ	37	50	15	54.0	1.34	134	100
XBD 14.0/ 15GJ	45	60	15	54.0	1.40	140	100
XBD 14.8/ 15GJ	45	60	15	54.0	1.48	148	100
XBD 16.4/ 15GJ	45	60	15	54.0	1.64	164	100
XBD 3.4/ 20GJ	11	15	20	72.0	0.34	34	100
XBD 4.0/ 20GJ	15	20	20	72.0	0.40	40	100
XBD 4.5/ 20GJ	15	20	20	72.0	0.45	45	100
XBD 5.1/ 20GJ	18.5	25	20	72.0	0.51	51	100
XBD 5.6/ 20GJ	22	30	20	72.0	0.56	56	100
XBD 6.5/ 20GJ	22	30	20	72.0	0.65	65	100
XBD 7.0/ 20GJ	22	30	20	72.0	0.70	70	100
XBD 7.5/ 20GJ	22	30	20	72.0	0.75	75	100
XBD 8.2/ 20GJ	30	40	20	72.0	0.82	82	100
XBD 9.0/ 20GJ	30	40	20	72.0	0.90	90	100
XBD 9.4/ 20GJ	37	50	20	72.0	0.94	94	100
XBD 10.4/ 20GJ	37	50	20	72.0	1.04	104	100
XBD 11.3/ 20GJ	37	50	20	72.0	1.13	113	100
XBD 12.0/ 20GJ	37	50	20	72.0	1.20	120	100
XBD 12.7/ 20GJ	45	60	20	72.0	1.27	127	100
XBD 13.0/ 20GJ	55	75	20	72.0	1.30	130	100
XBD 13.8/ 20GJ	55	75	20	72.0	1.38	138	100
XBD 15.0/ 20GJ	75	100	20	72.0	1.50	150	100
XBD 17.0/ 20GJ	90	120	20	72.0	1.70	170	100
XBD 4.0/ 25GJ	18.5	25	25	90.0	0.40	40	100
XBD 4.6/ 25GJ	22	30	25	90.0	0.46	46	100
XBD 5.0/ 25GJ	22	30	25	90.0	0.50	50	100
XBD 6.0/ 25GJ	22	30	25	90.0	0.60	60	100
XBD 7.0/ 25GJ	30	40	25	90.0	0.70	70	100
XBD 8.0/ 25GJ	37	50	25	90.0	0.80	80	100
XBD 9.3/ 25GJ	37	50	25	90.0	0.93	93	100
XBD 10.0/ 25GJ	45	60	25	90.0	1.00	100	100
XBD 11.0/ 25GJ	45	60	25	90.0	1.10	110	100
XBD 11.6/ 25GJ	55	75	25	90.0	1.16	116	100
XBD 12.3/ 25GJ	55	75	25	90.0	1.23	123	100
XBD 14.0/ 25GJ	75	100	25	90.0	1.40	140	100
XBD 16.3/ 25GJ	90	120	25	90.0	1.63	163	100
XBD 3.2/ 30GJ	15	20	30	108.0	0.32	32	150
XBD 4.1/ 30GJ	18.5	25	30	108.0	0.41	41	150
XBD 4.7/ 30GJ	22	30	30	108.0	0.47	47	150

MODEL	Power		Flow		Head		Port
	z		L/s	m3/h	Mpa	m	mm
XBD 5.2/ 30GJ	30	40	30	108.0	0.52	52	150
XBD 6.0/ 30GJ	30	40	30	108.0	0.60	60	150
XBD 7.0/ 30GJ	37	50	30	108.0	0.70	70	150
XBD 8.0/ 30GJ	37	50	30	108.0	0.80	80	150
XBD 8.7/ 30GJ	45	60	30	108.0	0.87	87	150
XBD 9.1/ 30GJ	45	60	30	108.0	0.91	91	150
XBD 10.5/ 30GJ	55	75	30	108.0	1.05	105	150
XBD 11.3/ 30GJ	55	75	30	108.0	1.13	113	150
XBD 12.2/ 30GJ	75	100	30	108.0	1.22	122	150
XBD 13.6/ 30GJ	75	100	30	108.0	1.36	136	150
XBD 14.0/ 30GJ	90	120	30	108.0	1.40	140	150
XBD 15.8/ 30GJ	110	150	30	108.0	1.58	158	150
XBD 3.2/ 35GJ	18.5	25	35	126.0	0.32	32	150
XBD 4.4/ 35GJ	22	30	35	126.0	0.44	44	150
XBD 5.2/ 35GJ	30	40	35	126.0	0.52	52	150
XBD 6.0/ 35GJ	37	50	35	126.0	0.60	60	150
XBD 6.6/ 35GJ	37	50	35	126.0	0.66	66	150
XBD 8							